GOVERNMENT OF INDIA DEPARTMENT OF SPACE INDIAN INSTITUTE OF REMOTE SENSING IIRS DEHRADUN PURCHASE & STORES

Ph No: 0135 - 2524317, 4318 Fax 0135 - 2748041 Email: pns@iirs.gov.in

Date : 29/09/2014

INVITATION TO TENDER

M/s

000000

 Our Ref No : GIRS
 2014-000213-01

 Tender Due: 15:00
 Hrs
 ISTon 21/10/2014

Dear Sirs,

Please submit your sealed quotation , in the Tender Form enclosed here along with the descriptive catalogues /

pamphlets /literature ,superscribed with Our Ref.No. and Due Date for the supply of the following items as per

the terms & conditions mentioned in Annexure(Form No:

S.No.	. Description of Items with Specifications	Unit	Quantity
1	Dagu Wild Thumper 6WD All Terrain Chassis (Specifications as per annexure enclosed)	NOS.	1

DELIVERY AT: IIRS

MODE OF DESPATCH DOOR DLVRY

DUTY EXEMPTIONS

SPECIAL INSTRUCTIONS NIL

SPECIFIC TERMS

V:V: NARAYANAN KUTTY PURS. & STORES OFFICER For and on behalf of the President of India The Purchaser

Terms & Conditions:

- 1. Material should be delivered & installed at IIRS
- 2. Payment will be made within 30 days from date of receipt of supply and acceptance of the material for orders value upto Rs.2.0 lakhs.
- 3. We cannot furnish Form C/D. Please indicate the applicable percentage of Trade tax / VAT in your quotation, if applicable. Otherwise the quoted rate will be considered as inclusive of all taxes.
- 4. Clearly mention the Make / Brand of the item in your quotation. Please enclosed the Authorization Certificate from the principal of the quoted Make / Model along with the quotation.
- 5. Also clearly mention the exact delivery period and validity of your offer shall be min 60 days.

GOVERNMENT OF INDIA DEPARTMENT OF SPACE INDIAN INSTITUTE OF REMOTE SENSING IIRS DEHRADUN PURCHASE & STORES

INDENTNO 2014000213

DESCRIPTION

DAGU WILD THUMPER 6WD

Dagu Wild Thumper 6WD All Terrain Chassis with following Specifications:

- 1- Maximum load: 5KG
- 2- Gear Box Speed Ratio: 34:1
- 3- Rated Voltage: 6V DC (Min. 2V Max. 7.5V)
- 4- Stall current: maximum 5.5A
- 5- Maximum Locked Current of 5.5A
- 6- No Load current per motor: 350mA
- 7- Motor RPM: 10000 + / -5%
- 8- Output shaft speed: 295rpm + / -5%
- 9- Stall torque is 4Kg/cm
- 10- Spiked tractor tyres
- 11- Super Twist" suspension system
- 12- Locked-rotor torque: 4Kg/cm